

OPERATION & MAINTENANCE MANUAL

DFI No. : D00190

Facility Type: Detention Tank/Pipe



OCTOBER, 2011

INDEX

1. IDENTIFICATION..... 1

2. FACILITY CONTACT INFORMATION..... 1

3. CONSTRUCTION..... 1

4. STORM DRAIN SYSTEM AND FACILITY OVERVIEW 2

5. FACILITY HAZ MAT SPILL FEATURE(S)..... 4

6. AUXILIARY OUTLET (HIGH FLOW BYPASS)..... 4

7. MAINTENANCE REQUIREMENTS..... 5

8. WASTE MATERIAL HANDLING..... 5

APPENDIX A: Operational Plan and Profile Drawing(s)

APPENDIX B: ODOT Project Plan Sheets

1. Identification

Drainage Facility ID (DFI): **D00190**

Facility Type: Detention Tank/Pipe

Construction Drawings: (V-File Number) [39V-063]

Location: District: 2B (Old 2A)

Highway No.: 140

Mile Post: [5.45 (beg./end)]

Description: This facility is located along the northeast quadrant of the intersection of Farmington Road and the Hillsboro-Silverton Hwy (OR 219) when heading eastbound onto Farmington Road. Access may be obtained from the left shoulder of Farmington Road.

2. Facility Contact Information

Contact the Engineer of Record, Region Technical Center, or Geo-Environmental's Senior Hydraulics Engineer for:

- Operational clarification
- Maintenance clarification
- Repair or restoration assistance

Engineering Contacts:

Region Technical Center Hydro Unit Manager

Or

Geo-Environmental Senior Hydraulics Engineer (503) 986-3365.

3. Construction

Engineer of Record: Consultant Designer – David Evans and Assoc., Inc., Richard Attanasio, P.E., 503-223-6663

Facility construction: 2006

Contractor: Kerr Contractors, Inc.

4. Storm Drain System and Facility Overview

A detention facility is designed to control the quantity of runoff, by reducing the peak discharge and only detaining runoff for some short period of time. These facilities are designed to store and gradually release or attenuate stormwater runoff via a control structure or release mechanism, and completely drain after the design storm has passed. The most common detention facilities include:

- Dry ponds - these are depressed storage areas that store runoff during wet weather and are dry the rest of the time. Usually they are earthen depressions.
- Tanks - these are underground storage facilities that are typically constructed from large diameter pipe.
- Vaults - these are enclosed underground storage facilities. They are typically constructed from reinforced concrete.

This facility is located on the northeast quadrant of the intersection of Farmington Road and the Hillsboro-Silverton Hwy (OR 219) when heading eastbound onto Farmington Road. Access may be obtained from the left shoulder of Farmington Road.

Water is collected by the surrounding ditches and sheet flows from impervious surfaces to catch basin inlets before being conveyed by a 12-inch storm drain system to the detention facility. The detention tank/pipe facility is comprised of two standard manholes on either side of two 60-inch diameter pipes with a flow-control structure at the center to regulate how flows are released to a nearby water quality manhole.

The system is designed to detain most stormwater events and lower flows on a continual basis. Stormwater from excessive higher flow events will overtop the concrete overflow weir, located within the flow control manhole, and leave the detention tank/pipe system before entering the water quality manhole (DFI D00191) to the east.

The water quality manhole is a specialized proprietary structure designed to treat and remove pollutants from the stormwater. Once treated, the water flows south through a 12-inch outlet pipe toward an outfall and riprap pad before entering a ditch that directs flows to Christensen Creek; see Points A and C of the Operational Plan, Appendix A.

A. Maintenance equipment access:

Unobstructed access may be obtained from the left shoulder of Farmington Road just east of its intersection with the Hillsboro-Silverton Highway (OR 219).

B. Heavy equipment access into facility:

- Allowed (no limitations)
- Allowed (with limitations)
- Not allowed

C. Special Features:

- Amended Soils
- Porous Pavers
- Liners
- Underdrains



Photo 1: Looking southwest at flow control manhole structure; Point A, Ops Plan.



Photo 2: Looking northwest at water quality and flow control manhole structures.

5. Facility Haz Mat Spill Feature(s)

The detention tank/pipe (DFI D00190) and the adjoining water quality manhole facility (DFI D00191) can be used to store a volume of liquid by blocking the 12-diameter outlet pipes located at either the outlet of the flow control detention manhole, or at the water quality manhole. These pipes are associated with Point C on the Operational Plan, Appendix A.

6. Auxiliary Outlet (High Flow Bypass)

Auxiliary Outlets are provided if the primary outlet control structure can not safely pass the projected high flows. Broad-crested spillway weirs and over flow risers are the two most common auxiliary outlets used in stormwater treatment facility design. The auxiliary outlet feature is either a part of the facility or an additional storm drain feature/structure.

The auxiliary outlet feature for this facility is:

Designed into facility

The auxiliary outlet is designed into the system's flow control manhole and overflow weir located at the center of the detention tank/pipe. In the event of high flows, stormwater overtops the overflow weir and exits the facility through a 12-inch pipe; see Point A on the Operational Plan, Appendix A.

Other, as noted below

7. Maintenance Requirements

Routine maintenance table for non-proprietary stormwater treatment and storage/detention facilities have been incorporated into ODOT's Maintenance Guide. These tables summarize the maintenance requirements for ponds, swales, filter strips, bioslopes, and detention tanks and vaults. Special maintenance requirements in addition to the routine requirements are noted below when applicable.

The ODOT Maintenance Guide can be viewed at the following website:

<http://www.oregon.gov/ODOT/HWY/OOM/MGuide.shtml>

Maintenance requirements for proprietary structures, such as underground water quality manholes and/or vaults with filter media are noted in Appendix C when applicable.

The following stormwater facility maintenance table (See ODOT Maintenance Guide) should be used to maintain the facility outlined in this Operation and Maintenance Manual or follow the Maintenance requirements outlined in Appendix C when proprietary structure is selected below:

- Table 1 (general maintenance)
- Table 2 (stormwater ponds)
- Table 3 (water quality biofiltration swales)
- Table 4 (water quality filter strips)
- Table 5 (water quality bioslopes)
- Table 6 (detention tank)
- Table 7 (detention vault)
- Appendix C (proprietary structure)
- Special Maintenance requirements

Note: Special maintenance Requirements Require Concurrence from ODOT SR Hydraulics Engineer.

8. Waste Material Handling

Material removed from the facility is defined as waste by DEQ. Refer to the roadwaste section of the ODOT Maintenance Yard Environmental Management System (EMS) Policy and Procedures Manual for disposal options: <http://egov.oregon.gov/ODOT/HWY/OOM/EMS.shtml>



Contact any of the following for more detailed information about management of waste materials found on site:

ODOT Clean Water Unit	(503) 986-3008
ODOT Statewide Hazmat Coordinator	(503) 229-5129
ODOT Region Hazmat Coordinator	(503) 731-8290
ODEQ Northwest Region Office	(503) 229-5263



Appendix A

Content:

- **Operational Plan and Profile Drawing(s)**



Flow Control Detention Manhole Detail



- LEGEND:**
- ◉ Photo Location / Direction
 - Ⓐ Flow Control Detention Manhole
 - Ⓑ 60" Detention Pipe
 - Ⓒ Outlet of Detention Manhole is 12" Pipe Which Connects to Water Quality Manhole (DFI D00191)
 - ▒ Riprap Pad
 - ◉ and ◊ Manhole
 - and □ Inlet
 - Storm Pipe (Facility)
 - Storm Pipe
 - Conveyance Direction
 - ~ Pavement / Facility Flow Path

Sht. 1 of 1 OREGON DEPARTMENT OF TRANSPORTATION

Prepared By: J. D. Koziol
Drafted By: Jim Holeman

DFI D00190
MAINTENANCE DISTRICT 2B HWY 140
DETENTION TANK/PIPE
HILLSBORO-SILVERTON HIGHWAY MP 5.45
WASHINGTON COUNTY

Appendix B

Content:

- **ODOT Project Plan Sheets**
 - *Cover/Title Sheet*
 - *Water Quality/Detention Plan Sheets*
 - *Other Details*

STATE OF OREGON
 DEPARTMENT OF TRANSPORTATION
 PLANS FOR PROPOSED PROJECT


GRADING, DRAINAGE, STRUCTURE, PAVING, SIGNING, & ROADSIDE DEVELOPMENT

**OR219: HILLSBORO - SILVERTON HIGHWAY
 AT FARMINGTON ROAD**

HILLSBORO - SILVERTON HIGHWAY

WASHINGTON COUNTY

JULY 2006



Overall Length Of Project - 0.99 km (0.61Miles)



ATTENTION:
 Oregon Law Requires You To Follow Rules Adopted By The Oregon Utility Notification Center. Those Rules Are Set Forth In OAR 952-001-0010 Through OAR 952-001-0090. You May Obtain Copies Of The Rules By Calling The Center. (Note: The Telephone Number For The Oregon Utility Center Is (503) 232-1987.)



INDEX OF SHEETS	
SHEET NO.	DESCRIPTION
1	Title Sheet
1A	Index Of Sheets Cont'd. & Std. Drg. Nos.

BEGINNING OF PROJECT
 STA. 8+189.00 (M.P. 5.18)

END OF PROJECT
 STA. 9+175.00 (M.P. 5.79)



OREGON TRANSPORTATION COMMISSION

Stuart Foster CHAIRMAN
 Gail L. Achterman COMMISSIONER
 Mike Nelson COMMISSIONER
 Randall Pape COMMISSIONER
 Janice J. Wilson COMMISSIONER
 Matthew L. Garrett DIRECTOR OF TRANSPORTATION

REGISTERED PROFESSIONAL ENGINEER
 13,704
Catherine M. Nelson
 OREGON
 JULY 16, 1987
 CATHERINE M. NELSON
 Expires Dec. 31, 2006

Catherine M. Nelson
 TECHNICAL SERVICES MANAGING ENGINEER


**OR219: HILLSBORO-SILVERTON HIGHWAY
 AT FARMINGTON ROAD**
 HILLSBORO - SILVERTON HIGHWAY
 WASHINGTON COUNTY

FEDERAL HIGHWAY ADMINISTRATION	PROJECT NUMBER	SHEET NO.
OREGON DIVISION	X-STP-S140 (032)	1




Sec. 31, T. 1S, R. 2W, W.M.

SEE SHT. AF
MATCH LINE



BRIDGE DETAILS CHECKED



Plug & Abandon Pipe
Shown Thus:

DAVID EVANS AND ASSOCIATES INC.

OREGON DEPARTMENT OF TRANSPORTATION
ROADWAY ENGINEERING SECTION

**OR219: HILLSBORO - SILVERTON HIGHWAY
AT FARMINGTON ROAD**

HILLSBORO - SILVERTON HIGHWAY
WASHINGTON COUNTY

Reviewed By - *CAH*
Designed By - SRV
Drafted By - MJY

REGISTERED PROFESSIONAL
ENGINEER
15058

OREGON
JULY 25, 1990


RICHARD ATTANASIO

EXPIRES 12-31-07

DRAINAGE PLAN


SHEET NO.
4B

- ① Sta. 8+442.2, Rt. (8.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 47.5 m
1.5 m Depth
- ② Sta. 8+472.9, Rt. (7.7 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 30.2 m
1.5 m Depth
- ③ Sta. 8+492.1, Rt. (7.6m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 19.0 m
1.5 m Depth
- ④ Sta. 8+535.5, Rt. (8.6 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 42.6 m
1.5 m Depth
- ⑤ Sta. 8+498.0 To Sta. 8+594.1, Rt.
Const. Asph. Conc. Drainage Curb
(See Drg. No. RD700)
- ⑥ Sta. 8+577, Rt. (9.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 41.0 m
1.5 m Depth
- ⑦ Sta. 8+580, Rt. (9.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 3.0 m
1.5 m Depth
- ⑧ Sta. 8+585, Rt. (9.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 5.0 m
1.5 m Depth
- ⑨ Sta. 8+590, Rt. (9.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 5.0 m
1.5 m Depth
(See Drg. No. RD364)
- ⑩ Sta. 8+622.85, Rt. (4.4 m)
Const. Manhole, Large 2100 mm Dia.
Inst. 300 mm Sew. Pipe - 33.2 m
1.5 m Depth
Inst. 300 mm Sew. Pipe - 23.0 m
1.5 m Depth
(See Drg. No. RD346)
- ⑪ Sta. 8+705 To Sta. 8+788.0, Lt.
Const. Asph. Conc. Drainage Curb
- ⑫ Sta. 8+633.70 To Sta. 8+643.14, Lt
Const. Asph. Conc. Drainage Curb
- ⑬ Sta. 8+638, Lt. (14.0 m)
Const. Type "G-2" Inlet
- ⑭ Sta. 8+635, Rt. (16.0 m)
Const. Type "G-2" Inlet
Inst. 300 mm Sew. Pipe - 3.5 m
1.5 m Depth
- ⑮ Sta. "F2" 8+598.20, Lt. (20.8 m)
Const. Outfall
Inst. 300 mm Sew. Pipe - 18.0 m
3.0 m Depth
Const. Loose Riprap (Class 25) - 1.44 m³
(2.4 m Long x 1.2 m Wide x 0.5 m Deep)
- ⑯ Sta. "F2" 8+590.50, Lt. (4.5 m)
Const. Manhole, Type Water Quality
Inst. 300 mm Sew. Pipe - 10.4 m
3.0 m Depth
- ⑰ Fill Abandoned Structures
- ⑱ Sta. "F2" 8+521.24, Rt. (3.8 m)
Const. Manhole, Large 2100 mm Dia.
Inst. 300 mm Sew. Pipe - 12.9 m
1.5 m Depth
- ⑲ Sta. "F2" 8+473, Lt.
Inst. 300 mm Culv. Pipe - 8.4 m
1.5 m Depth
- ⑳ Sta. "F2" 8+524, Rt. (16.8 m)
Const. Type "D" Inlet
(See Drg. No. RD370)
- ㉑ Sta. "F2" 8+590.80, Rt. (5.8 m)
Const. Manhole, Type Flow Control, 3000 mm
Inst. 300 mm Sew. Pipe - 5.5 m
1.5 m Depth
Inst. 1500 mm Sew. Pipe - 68.0 m
6.0 m Depth
Inst. 1500 mm Sew. Pipe - 37.0 m
3.0 m Depth
(For Details, See Sht. GJ)
- ㉒ Sta. "F2" 8+593, Rt. (10.5 m)
Const. Type "G-2M" Inlet
(See Drg. No. RD364)




DAVID EVANS AND ASSOCIATES INC.	
OREGON DEPARTMENT OF TRANSPORTATION ROADWAY ENGINEERING SECTION	
OR219: HILLSBORO - SILVERTON HIGHWAY AT FARMINGTON ROAD HILLSBORO - SILVERTON HIGHWAY WASHINGTON COUNTY	
Reviewed By - CAI Designed By - SRV Drafted By - MJT	
DRAINAGE PLAN NOTES	SHEET NO. 4C

"F2" Line



8+500

8+600



DAVID EVANS AND ASSOCIATES INC.

OREGON DEPARTMENT OF TRANSPORTATION
ROADWAY ENGINEERING SECTION

OR219: HILLSBORO - SILVERTON HIGHWAY
AT FARMINGTON ROAD

HILLSBORO - SILVERTON HIGHWAY

WASHINGTON COUNTY

Reviewed By - MJH

Designed By - DYH


Drafted By - MJY

PROFILE


SHEET NO.

4E




FLOW CONTROL MANHOLE



VORTEX VALVE DETAIL



SECTION A-A (NTS)



DAVID EVANS AND ASSOCIATES INC.	
OREGON DEPARTMENT OF TRANSPORTATION ROADWAY ENGINEERING SECTION	
OR219: HILLSBORO - SILVERTON HIGHWAY AT FARMINGTON ROAD	
HILLSBORO - SILVERTON HIGHWAY WASHINGTON COUNTY	
Reviewed By - <i>GH</i>	STRUCTURE NO.
Designed By - SRV	BRIDGE D.W.C. NO.
Drafted By - TASC	SHEET NO. GJ
DRAINAGE DETAILS	