

OPERATION & MAINTENANCE MANUAL

DFI No. : D00238

**Facility Type: Water Quality Biofiltration
Swale**



JUNE, 2011

INDEX

1. IDENTIFICATION..... 1

2. FACILITY CONTACT INFORMATION..... 1

3. CONSTRUCTION..... 1

4. STORM DRAIN SYSTEM AND FACILITY OVERVIEW 2

5. FACILITY HAZ MAT SPILL FEATURE(S)..... 4

6. AUXILIARY OUTLET (HIGH FLOW BYPASS)..... 4

7. MAINTENANCE REQUIREMENTS..... 5

8. WASTE MATERIAL HANDLING..... 5

APPENDIX A: Operational Plan and Profile Drawing(s)

APPENDIX B: ODOT Project Plan Sheets

1. Identification

Drainage Facility ID (DFI): **D00238**
Facility Type: Water Quality Biofiltration Swale
Construction Drawings: (V-File Number) 26V-092
Location: District: 1 (Old 2A)
Highway No.: 092
Mile Post: 25.90; 25.95 (beg./end)
Description: This facility is located along the west side the Columbia River Highway (Hwy. 092) adjacent to the southbound travel lane just south of Bay Hill Lane. Unobstructed access can be obtained from the right shoulder of the roadway.

2. Facility Contact Information

Contact the Engineer of Record, Region Technical Center, or Geo-Environmental's Senior Hydraulics Engineer for:

- Operational clarification
- Maintenance clarification
- Repair or restoration assistance

Engineering Contacts:

Region Technical Center Hydro Unit Manager

Or

Geo-Environmental Senior Hydraulics Engineer (503) 986-3365.

3. Construction

Engineer of Record: Consultant Designer - W&H Pacific, William Evans, P.E., (503) 362-4675

Facility construction: 1996

Contractor: N/A

4. Storm Drain System and Facility Overview

A water quality swale is a flat-bottomed open channel designed to treat stormwater runoff from highway pavement areas. This type of facility is lined with grass. Treatment by trapping sedimentation occurs when stormwater runoff flows through the grass.

This facility is located along the west side the Columbia River Highway (Hwy. 092) adjacent to the southbound travel lane just south of Bay Hill Lane. Unobstructed access can be obtained from the right shoulder of the roadway. The swale was constructed as part of an existing roadside ditch. Flows from both the roadway and ditch enter the swale from the south, overtopping riprap and a small 6-inch by 3-inch concrete knee wall flow spreader. As the water flows north it is treated as it slows and spreads out within the swale before entering a 15-inch culvert pipe just prior to Bay Hill Lane.

A. Maintenance equipment access:

Unobstructed access can be obtained from the right shoulder of southbound Hwy. 92.

B. Heavy equipment access into facility:

- Allowed (no limitations)
- Allowed (with limitations)
- Not allowed

C. Special Features:

- Amended Soils
- Porous Pavers
- Liners
- Underdrains



Photo 1: Looking north at water quality swale. Hwy 92 is located to the right.



Photo 2: Looking north at water quality swale near the swale entrance. Hwy 92 is located to the right.



Photo 3: Looking at the concrete knee wall near the entrance to the swale. Hwy 92 is located to the right.

5. Facility Haz Mat Spill Feature(s)

The water quality biofiltration swale can be used to store a volume of liquid by blocking the 15-inch culvert outlet pipe located at the outlet of the swale on the south side of Bay Hill Lane. There is also a type “M-E” inlet located on the north side of Bay Hill Lane and a 24-inch pipe, conveying water to the east that could be used for the same purposes. Sandbags may be one way to best accomplish this.

6. Auxiliary Outlet (High Flow Bypass)

Auxiliary Outlets are provided if the primary outlet control structure can not safely pass the projected high flows. Broad-crested spillway weirs and over flow risers are the two most common auxiliary outlets used in stormwater treatment facility design. The auxiliary outlet feature is either a part of the facility or an additional storm drain feature/structure.

The auxiliary outlet feature for this facility is:

Designed into facility

Other, as noted below

There is no auxiliary outlet feature for this facility.

7. Maintenance Requirements

Routine maintenance table for non-proprietary stormwater treatment and storage/detention facilities have been incorporated into ODOT's Maintenance Guide. These tables summarize the maintenance requirements for ponds, swales, filter strips, bioslopes, and detention tanks and vaults. Special maintenance requirements in addition to the routine requirements are noted below when applicable.

The ODOT Maintenance Guide can be viewed at the following website:

<http://www.oregon.gov/ODOT/HWY/OOM/MGuide.shtml>

Maintenance requirements for proprietary structures, such as underground water quality manholes and/or vaults with filter media are noted in Appendix C when applicable.

The following stormwater facility maintenance table (See ODOT Maintenance Guide) should be used to maintain the facility outlined in this Operation and Maintenance Manual or follow the Maintenance requirements outlined in Appendix C when proprietary structure is selected below:

- Table 1 (general maintenance)
- Table 2 (stormwater ponds)
- Table 3 (water quality biofiltration swales)
- Table 4 (water quality filter strips)
- Table 5 (water quality bioslopes)
- Table 6 (detention tank)
- Table 7 (detention vault)
- Appendix C (proprietary structure)
- Special Maintenance requirements:

Note: Special maintenance Requirements Require Concurrence from ODOT SR Hydraulics Engineer.

8. Waste Material Handling

Material removed from the facility is defined as waste by DEQ. Refer to the roadwaste section of the ODOT Maintenance Yard Environmental Management System (EMS) Policy and Procedures Manual for disposal options: <http://egov.oregon.gov/ODOT/HWY/OOM/EMS.shtml>





Contact any of the following for more detailed information about management of waste materials found on site:

ODOT Clean Water Unit	(503) 986-3008
ODOT Statewide Hazmat Coordinator	(503) 229-5129
ODOT Region Hazmat Coordinator	(503) 731-8304
ODEQ Northwest Region Office	(503) 229-5263

Appendix A

Content:

- **Operational Plan and Profile Drawing(s)**



- LEGEND:**
- Photo Location / Direction
 - Swale Inlet from Drainage Ditch
 - Water Quality Swale Outlet to 15-Inch Culvert
 - Manhole
 - Inlet
 - Storm Pipe (Facility)
 - Storm Pipe
 - Conveyance Direction
 - Pavement / Facility Flow Path
 - Traffic Direction / Flow

Prepared By: <u>Bob Knorr</u> Drafted By: <u>Bob Knorr</u>	DFI D00238 MAINTENANCE DISTRICT 1 HWY 92 WATER QUALITY BIOFILTRATION SWALE COLUMBIA HIGHWAY MP 25.90-25.95 COLUMBIA COUNTY
---	---

Appendix B






Content:

- **ODOT Project Plan Sheets**
 - *Cover/Title Sheet*
 - *Water Quality/Detention Plan Sheets*
 - *Other Details*

BIO-FILTER SWALE

Bio-Filter Swale Table

Station From	Station To	Left Or Right	Slope A	Slope B	Bottom Width (Ft)	Depth (Ft)	Length (Ft)	Channel Slope (%)
573+00	575+50	Rt	6:1	4:1	4	1	250	1.83
610+50	613+50	Rt	6:1	4:1	4	1	300	1.10
615+20	618+20	Rt	6:1	1 1/2:1	4	1	300	0.57
719+70	720+90	Rt	6:1	4:1	4	1	120	1.57
720+90	722+60	Rt	6:1	4:1	4	1	170	1.33
797+90	800+08	Lt	3:1	2:1	4	1	218	0.83
839+45	-	Lt	2:1	2:1	10	1	160	3.12
856+70	860+75	Lt	4:1	4:1	4	1	405	0.75-2.0
897+37	-	Lt	3:1	3:1	6	1	290	1.20
898+50	900+75	Rt	4:1	1 1/2:1	4	1	225	0.98




COLUMBIA CITY N.C.L. - WARREN SEC. COLUMBIA RIVER HIGHWAY (LOWER) COLUMBIA COUNTY		
FEDERAL HIGHWAY ADMINISTRATION	PROJECT NUMBER	SHEET NO.
REGION 10	OREGON DIVISION	2B-17

2B-17.DWG 05-OCT-1995 MOM

Sec. 17, T. 4N., R. 1W., W.M.


REVISED AS CONSTRUCTED
10/98 CONTRACT 11695



- ① Const. Road Conn. - 3
- ② Sta. 897+43, Rt.
Const. Type "M-E" Inlet
Inst. 24" Culv. Pipe - 115'
Const. Paved End Slope
Tr. Exc. - 60 C.Y.
(See Drg. No. 2105A)
- ③ Sta. 897+43, Lt.
Const. Loose Riprap (Class 100) - 3 C.Y.
- ④ Sta. "DIT" 10+00 To Sta. "DIT" 12+95
Const. Swale - 390 S.Y.
Dt. Exc. - 690 C.Y.
(For Profile, See Sheet 35B)
(For Details, See Sheet 2B-17)
- ⑤ Sta. "PRD" 6+70
Inst. 24" Culv. - 60'
Under Pvmt. - 20'
Tr. Exc. - 80 C.Y.
- ⑥ Const. Conc. R.R. Xing (By Others)
Inst. R.R. Xing Gate Signals - 2 (By Others)
- ⑦ Const. Guard Rail - 50' (Type 2A)
- 12.5' (Type 3)
Flare Rate=9:1, W=10', E=0
Const. Anchor (Type 1 Mod.)
Inst. End Piece (Type B)
Inst. SRT-100 End Terminal
- ⑧ Const. Guard Rail - 75' (Type 2A)
- 12.5' (Type 3)
Flare Rate=9:1, W=10', E=0
Const. Anchor (Type 1)
(Type 1 Mod.)
Inst. End Piece (Type B)
(Type C)
- ⑨ Const. Type "D" Inlet
- ⑩ Sta. "PRD" 15+50, Lt.
Const. Appr.
- ⑪ Inst. Multiple Mailbox Support
Const. Conc. Collar
- ⑫ Sta. 898+00, Rt.
Const. Appr.
Inst. 15" Culv. Pipe - 105'
Const. Paved End Slope
Const. Type "M-0" Inlet
Tr. Exc. - 40 C.Y.
(See Drg. No. 2105A)
- ⑬ Sta. 898+50 To Sta. 900+75, Rt.
Const. Swale - 235 S.Y.
Dt. Exc. - 120 C.Y.
(For Details, See Sheet 2B-17)
- ⑭ Inst. 24" Culv. Pipe - 85'

COLUMBIA CITY N.C.L. - WARREN SEC.			
COLUMBIA RIVER HIGHWAY (LOWER)			
COLUMBIA COUNTY			
FEDERAL HIGHWAY ADMINISTRATION		PROJECT NUMBER	SHEET NO.
REGION 10	OREGON DIVISION		35


03-OCT-1995 T.J.T. 35_PLAN.DGN



COLUMBIA CITY N.C.L. - WARREN SEC.			
COLUMBIA RIVER HIGHWAY (LOWER)			
COLUMBIA COUNTY			
FEDERAL HIGHWAY ADMINISTRATION		PROJECT NUMBER	SHEET NO.
REGION 10	OREGON DIVISION		35A


35A_PRO.DGN

10/98
TJT



100

'DIT' LINE
Const. Swale



COLUMBIA CITY N.C.L. - WARREN SEC.
COLUMBIA RIVER HIGHWAY (LOWER)
COLUMBIA COUNTY

FEDERAL HIGHWAY ADMINISTRATION		PROJECT NUMBER	SHEET NO.
REGION 10	OREGON DIVISION		35B

26-JUL-1995 T.JT

#####

35B_PRO.DGN