

OPERATION & MAINTENANCE MANUAL

DFI No. : D00674

Facility Type: Water Quality Extended
Detention Pond



[April, 2018]

INDEX

1. IDENTIFICATION..... 1

2. FACILITY CONTACT INFORMATION 1

3. CONSTRUCTION..... 1

4. STORM DRAIN SYSTEM AND FACILITY OVERVIEW 2

5. FACILITY HAZ MAT SPILL FEATURE(S)..... 4

6. AUXILIARY OUTLET (HIGH FLOW BYPASS)..... 4

7. MAINTENANCE REQUIREMENTS..... 5

8. WASTE MATERIAL HANDLING..... 5

APPENDIX A: Operational Plan and Profile Drawing

APPENDIX B: ODOT Project Plan Sheets

1. Identification

Drainage Facility ID (DFI): **D00674**
Facility Type: Water Quality Extended Detention Pond
Construction Drawings: (V-File Number) 46V-022
Location: District: 2B
Highway No.: 75
Mile Post: (5.03 to 5.06) Hwy 75
Description: This facility is located north of the Sunrise Corridor in the center island of the Bordeaux Lane turnaround, northwest of the intersection of Bordeaux Lane and Mather Road.

2. Facility Contact Information

Contact the Engineer of Record, Region Technical Center, or Geo-Environmental's Senior Hydraulics Engineer for:

- Operational clarification
- Maintenance clarification
- Repair or restoration assistance

Engineering Contacts:

Region Technical Center Hydro Unit Manager

Or

Geo-Environmental Senior Hydraulics Engineer (503) 986-3365.

3. Construction

Engineer of Record: Consultant Designer – [OBEC Consulting Engineers, Amy Jones, 971-634-2005]

Facility construction: [2014]
Contractor: Kerr Contractors, Inc.

4. Storm Drain System and Facility Overview

An extended detention dry pond is a basin that is designed to detain stormwater for a sufficient time to allow particles and attached pollutants to settle. The outlet control structure limits the rate of runoff leaving the pond by using an orifice. These facilities are designed to completely drain over a 48 hour period. The sizing of these facilities depends on the location and the amount of contributing impervious area.

This extended detention pond is designed to store runoff during wet weather and is dry the remainder of the time. It is located north of the Sunrise Corridor in the center island of the Bordeaux Lane turnaround, northwest of the intersection of Bordeaux Lane and Mather Road. Access to the facility is provided directly from Bordeaux Lane and the turnaround area.

There is one culvert that conveys stormwater runoff from paved areas along the Mather Road and Bordeaux Lane alignments into the detention pond. The locations of this is noted on the Operation Plan as point A in Appendix A

The pond consists of two chambers, each with its own outfall structure. Chamber A (east chamber) exits the pond through Outfall A which consists of a Type "D" inlet connected to 12-inch storm drain pipe. This connects to a manhole containing the flow control assembly. Outfall A serves as a positive outfall for low flow storm events. This connects to the storm drain pipe system in Bordeaux Lane. See Photo 1 and Points B and C on the Operational Plan in Appendix A. Higher storm events will spill over the riprap weir into Chamber B (west chamber). Outfall B is located in Chamber B and consists of a Type "D" inlet connected to a 12-inch storm drain pipe that connects to a manhole containing the flow control assembly. The pipe outfalls to an existing ditch.

The storm drain outlet pipe from the flow control manhole connects to the auxiliary outfall. The storm drain pipe from the auxiliary outfall is 16-inches in diameter and connects to a manhole connecting to the flow control manhole. These are shown in the Operational Plan in Appendix A. The receiving waterway for the outlet pipes is Dean Creek.

A. Maintenance equipment access:

The pond and outlet structures can be accessed from a Bordeaux Lane and the turnaround road surrounding the pond. See the road layout on the Operational Plan in Appendix A.

B. Heavy equipment access into facility:

Allowed (no limitations)

- Allowed (with limitations)
- Not allowed

C. Special Features:

- Amended Soils
- Porous Pavers
- Liners
- Underdrains




Photo 1: a view of extended detention pond facility, looking North toward Bordeaux Lane.




Photo 2: a view of extended detention pond facility, looking Southwest toward Sunrise corridor.

5. Facility Haz Mat Spill Feature(s)

The pond can be used to store a volume of liquid by blocking the 12-inch diameter outlet pipe with the Type “D” inlet located at the outfall structure in the middle of the south side of the pond. This pipe is noted as point C in the Operational Plan. A barrier such as a metal plate over the metal grate on the inlet could be used to prevent liquid from draining from the pond.

6. Auxiliary Outlet (High Flow Bypass)

Auxiliary Outlets are provided if the primary outlet control structure cannot safely pass the projected high flows. Broad-crested spillway weirs and over flow risers are the two most common auxiliary outlets used in stormwater facility design. The auxiliary outlet feature is either a part of the facility or an additional storm drain feature/structure.

The auxiliary outlet feature for this facility is:

Designed into facility

High flows exit the pond through the auxiliary outlet structure consisting of a type “D” inlet located in Chamber B. This inlet connects to the outfall pipe from the main outfall and flow control structure. See Photo 2 and Point G in the Operational Plan in Appendix A.

Other, as noted below

There is a 30 mil black plastic liner along the bottom and sides of the pond in both chambers to prevent contaminants from the underlying soils to mix with the runoff.

7. Maintenance Requirements

Routine maintenance table for non-proprietary stormwater treatment and storage/detention facilities have been incorporated into ODOT's Maintenance Guide. These tables summarize the maintenance requirements for ponds, swales, filter strips, bioslopes, and detention tanks and vaults. Special maintenance requirements in addition to the routine requirements are noted below when applicable.

The ODOT Maintenance Guide can be viewed at the following website:

<http://www.oregon.gov/ODOT/HWY/OOM/MGuide.shtml>

The following stormwater facility maintenance table (See ODOT Maintenance Guide) should be used to maintain the facility outlined in this Operation and Maintenance Manual:

- Table 1 (general maintenance)
- Table 2 (stormwater ponds)
- Table 3 (water quality biofiltration swales)
- Table 4 (water quality filter strips)
- Table 5 (water quality bioslopes)
- Table 6 (detention tank)
- Table 7 (detention vault)
- Appendix C (proprietary structure)
- Special Maintenance requirements

8. Waste Material Handling

Material removed from the facility is defined as waste by DEQ. Refer to the roadwaste section of the ODOT Maintenance Yard Environmental Management System (EMS) Policy and Procedures Manual for disposal options: <http://egov.oregon.gov/ODOT/HWY/OOM/EMS.shtml>

Contact any of the following for more detailed information about management of waste materials found on site:

ODOT Clean Water Unit	(503) 986-3008
ODOT Statewide Hazmat Coordinator	(503) 229-5129
ODOT Region Hazmat Coordinator	(503) 731-8290

ODEQ Northwest Region Office

















(503) 229-5263


Appendix A


Content:

- **Operational Plan and Profile Drawing**

LEGEND:

-  Photo Location / Direction
-  12" storm drain pipe outlet
-  Type "D" Inlet and 12" storm drain pipe outfall
-  Flow control manhole
-  Storm drain manhole
-  Type "D" Inlet and 12" storm drain pipe outfall
-  Flow control manhole
-  Auxiliary outfall - Type "D" inlet and 16" storm drain pipe outfall
-  Storm drain manhole
-  Manhole
-  Inlet
-  Storm Pipe (Facility)
-  Storm Pipe (Not connected to facility)
-  Storm Pipe (Existing)
-  Conveyance Direction
-  Pavement / Facility Flow Path



 OREGON DEPARTMENT OF TRANSPORTATION	
DFI D00674	
MAINTENANCE DISTRICT 2B HWY 75	
EXTENDED DETENTION POND	
SUNRISE CORRIDOR MP 5.03 TO 5.06	
CLACKAMAS COUNTY	


Prepared By:	Amy Jones
Drafted By:	Amy Jones

Appendix B

Content:

- **ODOT Project Plan Sheets**
 - *Cover/Title Sheet*
 - *Water Quality/Detention Plan Sheets*
 - *Other Details*

STATE OF OREGON
 DEPARTMENT OF TRANSPORTATION
 PLANS FOR PROPOSED PROJECT
**GRADING, DRAINAGE, STRUCTURES, PAVING, SIGNING,
 ILLUMINATION, SIGNALS & ROADSIDE DEVELOPMENT**



Overall Length Of Project - 3.90 Miles

INDEX OF SHEETS	
SHEET NO.	DESCRIPTION
1	Title Sheet
1A	Index Of Sheets Cont'd.

FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC.

**CLACKAMAS HWY.
 CLACKAMAS COUNTY
 MARCH 2013**


**BEGIN WORK
 JTA-STP-S171(030)
 STA. "SR1" 505+78**

**BEGIN WORK
 JTA-STP-S171(030)
 STA. "G" 463+00**

**END WORK
 JTA-STP-S171(030)
 STA. "G" 492+00**

**END WORK
 JTA-STP-S171(030)
 STA. "OR" 352+20**

**END WORK
 JTA-STP-S171(030)
 STA. "T" 705+75**



ATTENTION:
 Oregon Law Requires You To Follow Rules Adopted By The Oregon Utility Notification Center. Those Rules Are Set Forth In OAR 952-001-0010 Through OAR 952-001-0090. You May Obtain Copies Of The Rules By Calling The Center. (Note: The Telephone Number For The Oregon Utility Center is (503) 232-1987.)

**LET'S ALL
 WORK TOGETHER
 TO MAKE THIS
 JOB SAFE**

- OREGON TRANSPORTATION COMMISSION**
- Pat Egan CHAIR
 - David Lohman COMMISSIONER
 - Mary F. Olson COMMISSIONER
 - Mark Frohnmayer COMMISSIONER
 - Tammy Boney COMMISSIONER
 - Matthew L. Garrett DIRECTOR OF TRANSPORTATION

PLANS PREPARED FOR
 OREGON DEPARTMENT OF TRANSPORTATION

OBEC CONSULTING ENGINEERS
 CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-0089
 REGIONAL OFFICES: LAKE OSWEGO, SALEM, MEDFORD, OREGON; VANCOUVER, WASHINGTON

These plans were developed using ODOT design standards. Exceptions to these standards, if any, have been submitted and approved by the ODOT Chief Engineer or their delegated authority.

Approving Authority: *Lawrence H. Fox* 12/31/12
 Signature & date


LAWRENCE H. FOX - PROJECT MANAGER
 Print name and title

Concurrence by ODOT Chief Engineer

**FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC.
 CLACKAMAS HWY.
 CLACKAMAS COUNTY**

FEDERAL HIGHWAY ADMINISTRATION	PROJECT NUMBER	SHEET NO.
OREGON DIVISION	JTA-STP-S171(030)	1

SEC. 4, 5, 9, 10, 11
 T. 2 S., R. 2 E., W.M.



REGISTERED PROFESSIONAL
ENGINEER
73309
OREGON
MAY 13, 2003
TOM METCALF
EXPIRES: 12/31/14


OREGON DEPARTMENT OF TRANSPORTATION

OBEC CONSULTING ENGINEERS
CORPORATE OFFICE:
920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-6089
REGIONAL OFFICES:
LAKE OSWEGO, SALEM, MEDFORD, OREGON; VANCOUVER, WASHINGTON
www.obec.com


FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC.
CLACKAMAS HWY.
CLACKAMAS COUNTY

Design Team Leader - Tom Metcalf
Designed By - Jason Rahm/Alissa Loberg
Drafted By - Serban Dinca/Brittney Zornado

SHEET LAYOUT PLAN
SHEET NO. 1B




DFI D00674
 Extended
 Detention Pond
 SWM07




OREGON DEPARTMENT OF TRANSPORTATION	
OBEC CONSULTING ENGINEERS <small>www.obec.com</small>	
<small>CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-6089 REGIONAL OFFICES: LAKE OSWEGO, SALEM, MEDFORD, OREGON; VANCOUVER, WASHINGTON</small>	
FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC. CLACKAMAS HWY. CLACKAMAS COUNTY	
<small>Design Team Leader - Tom Metcalf Designed By - Ben Wewerka/Amy Jones Drafted By - Serban Dinca/Brittney Zornado</small>	
DRAINAGE & UTILITIES	SHEET NO. 7D

- ① Abandon pipe
- ② Remove inlet - 9
- ③ Remove manhole - 3
- ④ Sta. "SR2" 563+77.24, 8.71' Lt. to Sta. "SR2" 560+04.70, 6.9' Lt. Inst. 24" storm sew. pipe - 373' 10' depth
- ⑤ Sta. "SR2" 562+77.60, 55.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 34' 5' depth
- ⑥ Sta. "SR2" 562+77.64, 21.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 100' 5' depth
- ⑦ Sta. "SR2" 561+76.68, 55.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 34' 5' depth
- ⑧ Sta. "SR2" 561+77.36, 21.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 75' 5' depth
- ⑨ Sta. "SR2" 561+02.73, 21.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 51' 5' depth
- ⑩ Sta. "SR2" 560+51.91, 22' Rt. Const. type "G-2" inlet Inst. 18" storm sew. pipe - 48' 5' depth
- ⑪ Sta. "SR2" 561+02.59, 57.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 51' 5' depth
- ⑫ Sta. "SR2" 560+52.63, 58.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 49' 5' depth
- ⑬ Sta. "SR2" 560+03.23, 59.7' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 38' 5' depth
- ⑭ Sta. "SR2" 560+03.85, 21.9' Rt. Const. type "G-2" inlet Inst. 18" storm sew. pipe - 29' 5' depth
- ⑮ Sta. "SR2" 560+04.70, 6.9' Lt. Const. storm manhole 60" dia. Inst. 24" storm sew. pipe - 102' 10' depth
- ⑯ Sta. "SR2" 559+02.72, 1.6' Lt. Const. type "G-2" inlet Inst. 24" storm sew. pipe - 59' 5' depth
- ⑰ Sta. "SR2" 558+43.72, 6.9' Lt. Const. storm manhole Inst. 24" storm sew. pipe - 43' 5' depth
- ⑱ Sta. "SR2" 558+01.61, 11.7' Lt. Const. type "G-2" inlet Inst. 24" storm sew. pipe - 73' 5' depth
- ⑲ Sta. "SR2" 557+29.19, 11.9' Lt. Const. type "G-2" inlet Inst. 24" storm sew. pipe - 49' 5' depth
- ⑳ Sta. "SR2" 556+79.91, 12.1' Lt. Const. type "G-2" inlet Inst. 24" storm sew. pipe - 146' 5' depth
- ㉑ Sta. "SR2" 555+33.38, 10.68' Lt. Const. type "G-2" inlet Inst. 24" storm sew. pipe - 139' 10' depth
- ㉒ Sta. "SR2" 553+94.54, 6.9' Lt. Const. manhole 60" dia. with type "G-2" inlet Inst. 24" storm sew. pipe - 42' 10' depth
- ㉓ Sta. "SR2" 559+01.90, 34.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 67' 5' depth
- ㉔ Sta. "SR2" 558+35.10, 34.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 56' 5' depth
- ㉕ Sta. "SR2" 557+80, 34.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 49' 5' depth
- ㉖ Sta. "SR2" 557+31.29, 34.1' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 50' 5' depth
- ㉗ Sta. "SR2" 556+81.22, 34.2' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 50' 5' depth
- ㉘ Sta. "SR2" 556+31.46, 34.4' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 75' 10' depth
- ㉙ Sta. "SR2" 555+56.39, 35' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 75' 10' depth
- ㉚ Sta. "SR2" 554+82.15, 36.3' Rt. Const. manhole with type "G-2" inlet Inst. 15" storm sew. pipe - 102' 10' depth
- ㉛ Sta. "SR2" 553+81.10, 39.7' Rt. Const. manhole with type "G-2" inlet Inst. 15" storm sew. pipe - 7' 10' depth
- ㉜ Sta. "SR2" 553+82.69, 32.9' Rt. Const. storm manhole Inst. 24" storm sew. pipe - 270' 20' depth
- ㉝ Sta. "SR2" 550+80.98, 12.9' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 15' 10' depth
- ㉞ Sta. "SR2" 550+95.9, 11.8' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 44' 10' depth
- ㉟ Sta. "SR2" 550+99.05, 57.7' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 19' 10' depth
- ㊱ Sta. "SR2" 551+16.62, 50.2' Rt. Const. storm manhole 60" dia. Inst. 24" storm sew. pipe - 135' 20' depth
- ㊲ Sta. "SR2" 550+39.37, 159.1' Rt. Const. storm manhole 60" dia. Inst. 30" storm sew. pipe - 305' 5' depth (For additional details, see shts. GJ-2 & GJ-2A)
- ㊳ See sht. 6D, note 16 Inst. 16" storm sew. pipe
- ㊴ Sta. "SR2" 550+30.52, 145.45' Rt. to Sta. "SR2" 550+88.32, 136.6' Rt. Inst. 12" culv. pipe - 61' 5' depth Const. sloped end - 2 Const. paved end slope, Lt. & Rt.
- ㊵ Sta. "SR2" 548+90.78, 17.3' Lt. to Sta. "SR2" 550+26.81, 145.4' Rt. Inst. 36" culv. pipe - 215' 10' depth Const. sloped end - 2 Const. paved end slope, Lt. & Rt. (For profile see sht. 6E)
- ㊶ Const. storage pond, D00674 (SWM07) Inst. facility field markers, type S1 - 2 Inst. facility field markers, type S2 (For details, see sht. GJ-10)
- ㊷ Sta. "BX" 902+42.98, 19.31' Rt. Const. shallow manhole 24" dia. over extg. storm sew. pipe Inst. 12" storm sew. pipe - 79' 5' depth (See drg. no. RD342)
- ㊸ Sta. "BX" 903+26.96, 20.80' Rt. Const. shallow manhole Inst. 24" storm sew. pipe - 87' 5' depth
- ㊹ Sta. "BX" 904+24.55, 0.04' Rt. Const. shallow manhole over extg. storm sew. pipe
- ㊺ Sta. "BX" 903+32, 16.86' Rt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 35' 5' depth
- ㊻ Sta. "BX" 903+36.26, 18.67' Lt. Const. type "G-2" inlet Inst. 12" storm sew. pipe - 37' 5' depth
- ㊼ Sta. "BX" 903+65.41, 0.0' Rt. Const. shallow manhole 60" dia. Inst. 12" storm sew. pipe - 127' 5' depth Const. sloped end Const. paved end slope, Lt. Const. riprap basin (For details, see sht. GJ-22)
- ㊽ Sta. "BX" 905+48.74, 0.49' Lt. Const. shallow manhole 60" dia. over extg. storm sew. pipe
- ㊾ Relocate waterline (For details, see shts. WA-1 & WA-2)
- ㊿ Relocate sanitary sewer (For details, see sht. SA-4)
- 51 Preserve and protect gas line
- 52 Gas, cable, electric & telephone lines relocated prior to construction
- 53 Preserve and protect extg. communication conduit
- 54 Inst. impermeable check dam - 12 (For details, see sht. GJ-18)
- 55 Remove pipe - 192'
- 56 Sta. "BX" 902+74.40, 23.67' Rt. Const. shallow manhole 24" dia. over extg. sew. pipe Inst. 12" storm sew. pipe - 14' 5' depth Field verify extg. pipe depth
- 57 Sta. "BX" 902+89.78, 23.56' Rt. Const. type "CG-3" inlet Inst. 12" storm sew. pipe - 22' 5' depth Field adjust inlet flow line as necessary
- 58 Sta. "BX" 903+12.84, 23.40' Rt. Const. shallow manhole 24" dia. over extg. sew. pipe Field verify extg. pipe depth
- 59 Sta. "EAR" 92+18.77, 25.7' Rt. Const. shallow manhole




OREGON DEPARTMENT OF TRANSPORTATION	
	CONSULTING ENGINEERS <small>www.obec.com</small> CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-8089 REGIONAL OFFICES: LAKE OSWEGO; SALEM; MEDFORD, OREGON; VANCOUVER, WASHINGTON
FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC.	
CLACKAMAS HWY. CLACKAMAS COUNTY	
Design Team Leader - Tom Metcalf Designed By - Ben Wewerka/Amy Jones Drafted By - Serban Dinco/Brittney Zornado	
DRAINAGE & UTILITIES NOTES	SHEET NO. 7E

- ① Water quality WSE - 111.85
- ② 2 year WSE - 111.94
- ③ 10 year WSE - 112.02
- ④ 25 year WSE - 112.05
- ⑤ 100 year WSE - 112.09
(Via emergency spillway only)



"SWM07" PLAN
STORAGE POND, DF I-D00674



OREGON DEPARTMENT OF TRANSPORTATION


OBEC CONSULTING ENGINEERS
CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-6089
REGIONAL OFFICES: LAKE OSWEGO, SALEM, MEDFORD, OREGON; VANCOUVER, WASHINGTON
www.obec.com



FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC. CLACKAMAS HWY. CLACKAMAS COUNTY

Design Team Leader - Tom Metcalf
Designed By - Ben Wewerka/Amy Jones
Drafted By - Serban Dinca/Brittney Zornado



STORMWATER DETAILS

SHEET NO. GJ-10









"SWM07" OUTFALL STRUCTURE A DETAIL
DFI-D00674




"SWM07" FLOW CONTROL MANHOLE DETAIL
DFI-D00674




<p>OREGON DEPARTMENT OF TRANSPORTATION</p>	
<p>OBEC CONSULTING ENGINEERS www.obec.com</p>	<p>CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-6089 REGIONAL OFFICES: LAKE OSWEGO, SALEM, MEDFORD, OREGON / VANCOUVER, WASHINGTON</p>
<p>FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC. CLACKAMAS HWY. CLACKAMAS COUNTY</p>	
<p>Design Team Leader - Tom Metcalf Designed By - Ben Wewerka/Amy Jones Drafted By - Serban Dinca/Brittney Zornado</p>	
<p>STORMWATER DETAILS</p>	
<p>SHEET NO. GJ-10A</p>	



"SWM07" FLOW CONTROL MANHOLE
DFI-00674



"SWM07" OUTFALL STRUCTURE B DETAIL
DFI-D00674



CONSULTING ENGINEERS www.obec.com CORPORATE OFFICE: 920 COUNTRY CLUB ROAD, SUITE 100B EUGENE, OREGON 97401-6089 REGIONAL OFFICES: LAKE OSWEGO, SALEM, MEDFORD, OREGON, VANCOUVER, WASHINGTON	
FFO - OR212/224: SUNRISE CORRIDOR (I-205 - SE 122ND AVE) SEC. CLACKAMAS HWY. CLACKAMAS COUNTY	
Design Team Leader - Tom Metcalf Designed By - Ben Wewerka/Amy Jones Drafted By - Serban Dinca/Brittney Zornado	
STORMWATER DETAILS	SHEET NO. GJ-10B