OPERATION & MAINTENANCE MANUAL

DFI No.: D00877

Facility Type: Water Quality

Biofiltration Swale



[July, 2016]

INDEX

1.	IDENTIFICATION		1
2.	FACILITY CONTAC	CT INFORMATION	1
3.	CONSTRUCTION		1
4.	STORM DRAIN SY	STEM AND FACILITY OVERVIEW	2
5.	FACILITY HAZ MA	T SPILL FEATURE(S)	3
6.	AUXILIARY OUTLE	ET (HIGH FLOW BYPASS)	3
7.	MAINTENANCE RE	EQUIREMENTS	3
8.	WASTE MATERIAL	_ HANDLING	4
ΑP	PENDIX A:	Operational Plan and Section Draw	/ing(s)
ΑP	PENDIX B:	ODOT Project Plan S	Sheets

1. Identification

Drainage Facility ID (DFI): **D00877**

Facility Type: Water Quality Biofiltration Swale

Construction Drawings: (V-File Number) 49V-009

Location: District: 4

Highway No.: 009

Mile Post: 111.12 to111.14, Right

Description:

The facility is located on the west side of Hwy 101, between NE Highland Road and NE East Devils Lake Road. The facility can

be accessed via the shoulder of

southbound Hwy101.

2. Facility Contact Information

Contact the Engineer of Record (see section 3), Region Technical Center, or Geo-Environmental's Senior Hydraulics Engineer for:

- Operational clarification
- Maintenance clarification
- Repair or restoration assistance

Engineering Contacts:

Chris Carman, ODOT Hydraulics Engineer (503) 986-2691.

Or

Geo-Environmental Senior Hydraulics Engineer (503) 986-3365.

3. Construction

Engineer of Record: ODOT Designer – Region 2 Tech. Center,

Chris Carman, (503) 986-2691

Facility construction: 2015

Contractor: LRT Construciton LLC

4. Storm Drain System and Facility Overview

The swale is located 0.17 miles north of East Devils Lake Road on the west side of the Coast highway. Treatment of pollutants from the highway are achieved through sedimentation and infiltration through the water quality mix shown in section B-B in the operational plan.

A. Maintenance equipment access:

Maintenance crews and equipment can access the facility by parking on the shoulder of southbound Hwy101.



Heavy equipment access into facility:

- ☐ Not allowed

Heavy equipment access is allowed with limitations. Access is allowed for light to mid weight equipment such as mowers and small excavators.

	B. Special Features:
	☑ Amended Soils☐ Porous Pavers☐ Liners☐ Underdrains
5.	Facility Haz Mat Spill Feature(s) This facility has no Haz Mat spill features.
	The swale can be used to store a volume of liquid by blocking the outlet of the swale. A barrier such as a temporary berm made of sandbags could be used to prevent liquid from draining from the swale.
6.	Auxiliary Outlet (High Flow Bypass) Auxiliary Outlets are provided if the primary outlet control structure can not safely pass the projected high flows. Broad-crested spillway weirs and over flow risers are the two most common auxiliary outlets used in stormwater treatment facility design. The auxiliary outlet feature is either a part of the facility or an additional storm drain feature/structure.
	The auxiliary outlet feature for this facility is:
	□ Designed into facility
	☑ Other This facility does not contain an auxiliary outlet feature. The facility was

7. Maintenance Requirements

Routine maintenance table for non-proprietary stormwater treatment and storage/detention facilities have been incorporated into ODOT's Maintenance Guide. These tables summarize the maintenance requirements for ponds, swales, filter strips, bioslopes, and detention tanks and vaults. Special maintenance requirements in addition to the routine requirements are noted below when applicable.

designed to receive runoff from the road and discharge into cross pipes.

The ODOT Maintenance Guide can be viewed at the following website:

https://www.oregon.gov/ODOT/HWY/OOM/mg/02/act125_waterqualityfacilandtables.pdf

The following stormwater facility maintenance table (See ODOT Maintenance Guide) should be used to maintain the facility outlined in this Operation and Maintenance Manual or follow the Maintenance requirements outlined in Appendix C when proprietary structure is selected below:

⊠ Table 1 (general maintenance)
□ Table 2 (stormwater ponds)
oxtimes Table 3 (water quality biofiltration swales)
☐ Table 4 (water quality filter strips)
☐ Table 5 (water quality bioslopes)
☐ Table 6 (detention tank)
☐ Table 7 (detention vault)
□ Appendix C (proprietary structure)
☐ Special Maintenance requirements:

8. Waste Material Handling

Material removed from the facility is defined as waste by DEQ. Refer to the roadwaste section of the ODOT Maintenance Yard Environmental Management System (EMS) Policy and Procedures Manual for disposal options:

https://www.oregon.gov/ODOT/HWY/OOM/EMSdoc/ems_manual.pdf

Contact any of the following for more detailed information about management of waste materials found on site:

ODOT Clean Water Unit	(503) 986-3008
ODOT Statewide Hazmat Coordinator	(503) 667-7442
ODOT Region Hazmat Coordinator	(503) 731-8290
ODEQ Northwest Region Office	(503) 229-5263

Appendix A

Content:

• Operational Plan and Section Drawing(s)




Table 1: Swale Components		ID#
Manholes/Structures		
Pre-treatment manhole		S1
Weir type flow splitter/flow splitter manhole		S2
Orifice type flow splitter/flow splitter manhole		S3
Standard manhole		S4
Swale Inlet		
Pavement sheet flow		S5
Inlet Pipe (s)		S6
Open channel inlet		S7
Riprap pad	\boxtimes	S8
Ground Cover		
Grass bottom	\boxtimes	S9
Grass side slopes	\boxtimes	S10
Granular drain rock		S11
Plantings		S12
Underground Components		
Geotextile fabric		S13
Water quality mix	\boxtimes	S14
Perforated pipe		S15
Porous pavers (access grid)		S16
Flow Spreader		
Rock basin (used at inlet)		S17
Anchored board (midpoint of swale or every 50 feet along swale bottom)		S18
Other: earthen berms	\boxtimes	S19
Swale Outlet		
Catch basin with grate		S20
Outlet Pipe (s)		S21
Open channel outlet	\boxtimes	S22
Auxiliary Outlet: describe type		S23
Outfall Type		
	□ C	
Waterbody (Creek/Lake/Ocean)	□L	S24
,	□o	
Ditch		S25
Storm drain system		S26
Outfall Components		
Riprap pad		S27
Riprap bank protection		S28
1 1 1		

Appendix B

Content:

• ODOT Project Plan Sheets

49V-9

INDEX OF SHEETS SHEET NO. DESCRIPTION Title Sheet 1A Index Of Sheets Cont'd. & Std. Drg. Nos.

STATE OF OREGON DEPARTMENT OF TRANSPORTATION

PLANS FOR PROPOSED PROJECT

GRADING & PAVING

US101 @ N.E. DEVILS LAKE RD. SEC.

OREGON COAST HIGHWAY LINCOLN COUNTY

STA. "L"668+50 (M.P. 111.57)

Overall Length Of Project - 0.51 Miles

ATTENTION:

Oregon Law Requires You To Follow Rules
Adopted By The Oregon Utility Notification
Center. Those Rules Are Set Forth In
OAR 952-001-0010 Through OAR 952-001-0090.
You May Obtain Copies Of The Rules By Calling
The Center. (Note: The Telephone Number For
The Oregon Utility Center is (503) 232-1987.)

SE LET'S ALL WORK TOGETHER TO MAKE THIS JOB SAFE lp lip lip lip lip lip lip lip lip

OREGON TRANSPORTATION COMMISSION

Tammy Baney David Lohman Susan Morgan Alando Simpson

COMMISSIONER COMMISSIONER COMMISSIONER COMMISSIONER
DIRECTOR OF TRANSPORTATION

Sean O'Hollaren Motthew L. Carrett

These plans were developed using ODOT design standards. Exceptions to these standards, if any, have been submitted and approved by the ODOT Chief Engineer or their delegated


Signature & date

James E. West - R2 Tech Center Manager

Concurrence by ODOT Chief Engineer

US101 @ N.E. DEVILS LAKE RD. SEC. OREGON COAST HIGHWAY LINCOLN COUNTY


FEDERAL HIGHWAY ADMINISTRATION	PROJECT NUMBER	SHEET NO.
OREGON DIVISION	HSIP-S009(455)	1






49V-9

- (1) Sta. "WQ1" 0+24.1 to Sta. "WQ1" 1+23.5 Rt. Construct water quality biofiltration swale no.00877 Water Quality Mixture - 24 cu.yd. General excavation - 417 cu.yd.
- 2) Stormwater Facility Marker Types 1 and 2 DFI no.00877 (See dwg. RD399)
- Construct Riprap (Class 50) 3.5 yd.
- (4) Construct Riprap (Class 50) 4.5 yd.



SECTION A-A



RENEWS: 12-31-2015

SECTION B-B

Slopes shown as vertical to horizontal.



OREGON DEPARTMENT OF TRANSPORTATION

US101 @ N.E. DEVILS LAKE RD. SEC. OREGON COAST HIGHWAY
LINCOLN COUNTY


> Reviewer - Bruce Carmichael Designed By - Christopher Carmon Drafted By - Julie Rentz

REGION 2 TECH CENTER

STORMWATER PLAN

SHEET NO.





PLAN

